590.DCGE0830

SWITCH DISCONNECTOR
30A DC IP66/IP69 160x220x115mm
D3 IK09 GENERAL GREY/BLACK GW
650°C



EN IEC 60947-1 (2021)
EN IEC 60947-3 (2021)
Low voltage direct. 2014/35/EU

Commercial Series	ISOLATORS-PV Series
Synthetical description	SWITCH DISCONNECTOR
Type	GENERAL
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	30A
Poles	DC
Poles in series	8
Switch size	D3
Rated voltage	800V

PHYSICAL CHARACTERISTICS

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	ENGINEERING PLASTIC
Protection degree IP	IP66/IP69
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
GLOW WIRE	GW 650°C
Protection degree IK	IK09

DIMENSIONAL CHARACTERISTICS

Dimensions	160x220x115mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
Catalogue notes	Equipped with door interlock
Catalogue notes	Break-through cable entries on bottom side base
Catalogue notes	Reversible base
Catalogue notes	Blank side with drilling point marks on top side base