# 561.3286

INTERLOCKED SOCKET
32A 3P+E 6h 380-415V 60Hz 50Hz
106X240MM Screw terminals With mechanical interlock



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60309-4 (2007)
EN 60309-4/A1 (2012)

Low voltage direct. 2014/35/EU

| | |
|---|---|
| Commercial Series | ADVANCE 2 Series |
| Synthetical description | INTERLOCKED SOCKET |
| Mounting version | SURFACE MOUNTING |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Poles | 3P+E |
| Hour position | 6h |
| Rated voltage | 380-415V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | SURFACE MOUNTING |
| Colour | RED |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67 |
| Protection degree IK | IK07 |
| Contact material | CuZn (brass) |
| Cable entry | M25X1,5 |
| Padlock | ø5mm |

## DIMENSIONAL CHARACTERISTICS

| | |
|---|---|
| Flange | 106X240MM |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

## OPTIONS & VARIOUS NOTES

| | |
|---|---|
| Options | With mechanical interlock |
| Notes | WITHOUT FUSE HOLDER |
| Catalogue notes | Cable gland included |
| Catalogue notes | Threaded cap/cable sleeve included |
| Catalogue notes | Open threaded cable entry |



**SCAME PARRE S.p.A**
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000