505.6387

INTERLOCKED SOCKET
63A 3P+N+E 6h 346-415V 60Hz 50Hz
136X275MM_PAR Screw terminals
With mechanical interlock



EN 60309-4/A1 (2012)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60309-4 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)
Padlock	ø4,7mm

DIMENSIONAL CHARACTERISTICS

Flange	136X275MM_PAR

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER
Catalogue notes	Blank side with drilling point marks
Catalogue notes	Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.