## 248.1697

FLUSH MOUNTING APPLIANCE INLET
16A 3P+N+E 6h 346-415V 60Hz 50Hz 75X75MM Screw terminals



EN 60309-1 (1999)
EN 60309-2 (1999)
Low voltage direct. 2014/35/EU

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET |
| Mounting version | FLUSH MOUNTING |

### TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 16A |
| Poles | 3P+N+E |
| Hour position | 6h |
| Rated voltage | 346-415V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Screw terminals |

### PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | FLUSH MOUNTING |
| Colour | RED |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |

### DIMENSIONAL CHARACTERISTICS

| | |
|---|---|
| Flange | 75X75MM |

### DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

### OPTIONS & VARIOUS NOTES

| | |
|---|---|
| Catalogue notes | Version also available in black; just add “.K” at the end of the catalogue number. |