632.4520-000

MODULAR ENCLOSURE
IP66 SURFACE MOUNTING BLOCK4
11 MOD. 212x415x105mm



EN 60670-1 (2005)
EN 60670-24 (2013)
Low voltage direct. 2014/35/EU

Commercial Series	BLOCK Series
Synthetical description	MODULAR ENCLOSURE
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Dissipable power	14W

PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Mounting version	SURFACE MOUNTING
Protection degree IP	IP66
Protection degree IK	IK08

DIMENSIONAL CHARACTERISTICS

Modularity	BLOCK4
N.° modules	11 MOD.
Dimensions	212x415x105mm

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

OPTIONS & VARIOUS NOTES

Catalogue notes	50x60 mm cut-outs
Catalogue notes	Power dissipation calculated in conformity with IEC EN 62208 and IEC EN 60670-24 standards
Catalogue notes	70x87mm cut-outs
Catalogue notes	With cut-outs to contain 16A (70x87mm) or, with suitable adaption, 32A socket (84x106mm) and DOMOPLUS Series in the grey coloured positions

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000