213.3237RV

PLUG
32A 3P+N+E 6h 346-415V 60Hz 50Hz Screw terminals With REVERSE device



EN 60309-1/A1 (2007)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-2/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	OPTIMA-REVERSE Series
Synthetical description	PLUG
Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Options	With REVERSE device
Catalogue notes	Phase inverter
Catalogue notes	Operating principle of the phase inverter