513.1656

SURFACE MOUNTING SOCKET
16A 3P+E 6h 380-415V 60Hz 50Hz
Screw terminals



EN 60309-2/A1 (2007)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	OPTIMA-BASE Series
Synthetical description	SURFACE MOUNTING SOCKET
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M25X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
Catalogue notes	Rubber threaded cable sleeve included