518.1653T

SURFACE MOUNTING SOCKET
16A 2P+E 6h 200-250V 60Hz 50Hz
Screw terminals



EN 60309-2/A1 (2007)
EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M20X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Catalogue notes	Threaded break-through knock out