# 515.M6353

SURFACE MOUNTING SOCKET
63A 2P+E 6h 200-250V 50Hz 60Hz
Screw terminals



CE

EN 60309-2 (1999)
EN 60309-1 (1999)
Low voltage direct. 2014/35/EU

| | |
|---|---|
| Commercial Series | OPTIMA Series |
| Synthetical description | SURFACE MOUNTING SOCKET |
| Mounting version | FLUSH/SURFACE MOUNTING |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 63A |
| Poles | 2P+E |
| Hour position | 6h |
| Rated voltage | 200-250V |
| Working frequency | 50Hz |
| | 60Hz |
| Terminals | Screw terminals |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Mounting version | FLUSH/SURFACE MOUNTING |
| Colour | BLUE |
| Material | THERMOPLASTIC |
| Protection degree | Watertight |
| Protection degree IP | IP66/IP67/IP69 |
| Protection degree IK | IK08 |
| Types of available outlets | ANGLED |
| Contact material | CuZn (brass) |
| Cable entry | M32X1,5 |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]