201.CS2323-5

CHARGING CABLE
T2 32A 1P - T2 32A 1P
3G6+1x0,5mm² 5m 7,4kW



EN 50620 (2017)
EN 62196-2 (2017)
EN 62196-1 (2014)
EN 50620/A1 (2019)

Low voltage direct. 2014/35/EU

Commercial Series	LIBERA[CS] Series
Synthetical description	CHARGING CABLE
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW

TECHNICAL CHARACTERISTICS

Rated current	32A
Rated voltage	230V
Max power	7,4kW
Cable section	3G6+1x0,5mm²

PHYSICAL CHARACTERISTICS

Protection degree IP	IP44
Material	THERMOPLASTIC
Working temperature	-30°C/+50°C

DIMENSIONAL CHARACTERISTICS

Cable length	5m

INTERFACE, CONTROLS, FUNCTIONS AND EQUIPMENT

EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW
EV plug	Type 2 1P+N+E 32A 230V~
EV connector	Type 2 1P+N+E 32A 230V~

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Notes	T2 32A 1P - T2 32A 1P
Catalogue notes	IP rating of cable with rubber caps: IP54 IP rating within potted compound: IP67