# 201.CS2424-8

CHARGING CABLE
T2 32A 3P - T2 32A 3P
5G6+1x0,5mm² 7,5m 22kW



EN 50620 (2017)
EN 62196-2 (2017)
EN 62196-1 (2014)
EN 50620/A1 (2019)

Low voltage direct. 2014/35/EU

| | |
|---|---|
| Commercial Series | LIBERA[CS] Series |
| Synthetical description | CHARGING CABLE |
| EV standard | Type 2 3P+N+E 32A 400V~ 22kW |

## TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Rated current | 32A |
| Rated voltage | 400V |
| Max power | 22kW |
| Cable section | 5G6+1x0,5mm² |

## PHYSICAL CHARACTERISTICS

| | |
|---|---|
| Protection degree IP | IP44 |
| Material | THERMOPLASTIC |
| Working temperature | -30°C/+50°C |

## DIMENSIONAL CHARACTERISTICS

| | |
|---|---|
| Cable length | 7,5m |

## INTERFACE, CONTROLS, FUNCTIONS AND EQUIPMENT

| | |
|---|---|
| EV standard | Type 2 3P+N+E 32A 400V~ 22kW |
| EV plug | Type 2 3P+N+E 32A 400V~ |
| EV connector | Type 2 3P+N+E 32A 400V~ |

## DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

## OPTIONS & VARIOUS NOTES

| | |
|---|---|
| Notes | T2 32A 3P - T2 32A 3P |
| Catalogue notes | IP rating of cable with rubber caps: IP54<br>IP rating within potted compound: IP67 |